

INTERFACE ULTRA GRIP**81028-B00-XA330**

Description: Unsupported nitrile glove with a wave like surface texture having excellent grip in dry, wet and oil environments.

- Features & Benefits:
- * A wave like textured porous structure
 - * Unique surface texture to provide superior grip for all environments;dry,wet and oily conditions
 - * Improved dexterity due to porous structure
 - * Resist against hydrocarbons including petroleum derivatives,oil based chemicals
 - * Free of extractable protein
 - * Anatomically shaped for comfort
 - * Ingredients comply with FDA regulations for food contact
 - * Good abrasion resistance

Applications: Aerospace and Automobile Industry, Industrial Cleaning, Petrochemical Industry, Surface Coating, Chemical applications, Food processing and handling

Limitations: Keep the glove in dry condition after use

Elastomer: Nitrile rubber

Thickness: 0.28 +/- 0.05 mm

Lining: Unlined

Former: Plain

Exterior: Chlorinated

Cuff Types: Straight

Treatments: Chlorinated

Colours: Green G08/G35


AQL: 1.00

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016,EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	7	206	202	302	330
	8	222	220	306	330
	9	239	228	328	330
	10	260	252	342	330
	11	275	268	349	330
		Circumference in mm, +/- 10 mm		Tol. +/- 10 mm	

Shelf Life 1 Years

Protection against Chemical hazards	Performance	Degradation %
EN 374		
		
* Sodium hydroxide 40% (K)	Level 6	10.7
* n-Heptane (J)	Level 6	17.3
* Sulphuric acid 96% (L)	Level 3	51.9
* Nitric acid 65% (M)	Level 2	97.5
* Acetic acid 99% (N)	Level 2	98.1
* Ammonium hydroxide 25% (O)	Level 5	27.1
* Hydrogen peroxide 30% (P)	Level 6	20.5
* Hydrofluoric acid 40% (S)	Level 3	X
* Formaldehyde 37% (T)	Level 6	3.1

Note: Printed copies are valid only on the date printed

Printed Date: 05-Jan-2022

Revision:4

Published Date: 08-Nov-2021



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards		Performance
---------------------------------------	--	-------------

EN374



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 3
Level 0
Level 0
Level 1
X

Protection against Micro-organisms risk		Performance
---	--	-------------



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
n/a