## ESD PRO 21038-M00-GA330

Description: Unlined nitrile gloves

Features & Benefits:

- \* Static dissipative due to low vertical and low surface resistance
  \* Free from external conductive connections and adjustment systems
- \* Nitrile for reliable solvent resistance
- \* Specially formulated glove to disspate static charge, complies with EN 16350:2014
- \* Antistatic properties due to low surface resistance
- \* No latex allergy problems
- \* Straight cuff
- \* Manufactured under a stringent quality management system

Applications: Automotive Assembly, Spray paint industry, Spray powder industry

Elastomer: Nitrile rubber
Thickness: 0.38 +/- 0.05 mm
Lining: Unlined chlorinated
Former: Reverse Lozenge, CVIL
Exterior: Finished smooth

Cuff Types: Straight
Treatments: Chlorinated
Colours: Black D5

AQL - Critical: 1.5
Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment

against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018, EN ISO 21420:2020 and EN

16350:2014

Conforms to:

Physical	Size	Palm	Wrist	Cuff	Length
Dimensions:	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330
		Circumfe	Circumference in mm, +/- 10 mm		Tol. +/- 10 mm

Shelf Life 5 Years

<b>Protection against Chemical h</b>	otection against Chemical hazards Performance		Degradation %
EN 374-1/TYPE A			
	* n-Heptane (J)	Level 6	23.9
( ),#	* Sodium hydroxide 40% (K)	Level 6	-2.8
	* Sulphuric acid 96% (L)	Level 4	63.7
	* Nitric acid 65% (M)	Level 2	98.1
JKLMOPST	* Ammonium hydroxide 25% (O)	Level 5	18.1
	* Hydrogen peroxide 30% (P)	Level 5	-24.0
	* Hydrofluoric acid 40% (S)	Level 4	X
	* Formaldehyde 37% (T)	Level 6	-20.9

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023

Published Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964 Fax: +94-0122-699-018 E-Mail: postmast@dplgroup.com

Revision:12

## ESD PRO

21038-M00-GA330

## Protection against Mechanical hazards

EN 388



- \* Abrasion resistance
- \* Blade cut resistance
- \* Tear resistance
- \* Puncture resistance
- \* TDM cut resistance

Level 3

Performance

Level 0

Level 0

Level 1 X

Performance

## Protection against Micro-organisms risk

EN 374-5



\* Protection against bacteria and fungi

\* Protection against viruses

Passed

n/a

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964

> Fax: +94-0122-699-018 E-Mail: postmast@dplgroup.com

Published Date: 28-Nov-2023

Revision:12