

Description: Chlorinated heavy weight flock lined neoprene/natural rubber blended gloves

- Features & Benefits:
- * A blend of natural rubber and neoprene
 - * Anatomically shaped for comfort
 - * Anti-slip pattern for good grip in wet and dry conditions
 - * Compliant with (EC) No. 1935/2004 & EU 10/2011(Blue,Orange)
 - * Ingredients comply with FDA regulations for food contact (Blue only)
 - * Ingredients comply with FDA regulations for food contact (Orange O12 and Blue B3 only)
 - * Low in soluble proteins
 - * Manufactured under a stringent quality management system
 - * Pure cotton lining to absorb perspiration
 - * Straight cuff

Applications: Agriculture, Chemical Industry, Facility maintenance

Elastomer: Natural/Polychloroprene blended rubber

Thickness: 0.70 +/- 0.07 mm

Lining: Flocklined

Former: Honeycomb CIH

Exterior: Finished smooth

Cuff Types: Straight

Treatments: Chlorinated

Colours: Blue B3, Orange O12, Orange O4

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016,EN 388:2016+A1:2018 and EN ISO 21420:2020


Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	198	183	248	300
	7-7.5	208	190	251	300
	8-8.5	215	202	268	300
	9-9.5	235	226	280	300
	XL	250	237	293	310
	XXL	262	248	309	310

Circumference in mm, +/- 5 mm Tol. +/- 10 mm

Shelf Life 3 Years

EN 374-4

Protection against Chemical hazards	Performance	Degradation %
EN ISO 374-1/TYPE A		
 AKLMNPST		
* Methanol (A)	Level 2	15.5
* Sodium hydroxide 40% (K)	Level 6	-6.8
* Sulphuric acid 96% (L)	Level 4	21
* Nitric acid 65% (M)	Level 6	18.4
* Acetic acid 99% (N)	Level 3	23.4
* Hydrogen peroxide 30% (P)	Level 6	3.4
* Formaldehyde 37% (T)	Level 6	8.1
* Hydrofluoric acid 40% (S)	Level 6	X

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023


Revision:8

Published Date: 28-Nov-2023

Protection against Mechanical hazards **Performance**

<p>EN 388</p> 	<ul style="list-style-type: none"> * Abrasion resistance * Blade cut resistance * Tear resistance * Puncture resistance * TDM cut resistance 	<p>Level 3</p> <p>Level 1</p> <p>Level 1</p> <p>Level 0</p> <p>X</p>
---	---	--

Protection against Micro-organisms risk **Performance**

<p>EN ISO 374-5</p> 	<ul style="list-style-type: none"> * Protection against bacteria and fungi * Protection against viruses 	<p>Pass</p> <p>Pass</p>
---	---	-------------------------

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023

Revision:8

Published Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com