

Description: Unchlorinated/Chlorinated medium heavy weight flock lined natural rubber gloves

- Features & Benefits:
- * Natural rubber
 - * Anatomically shaped for comfort
 - * Pure cotton lining to absorb perspiration
 - * Anti-slip pattern for good grip in wet and dry conditions
 - * Pinked or straight cuff
 - * Ingredients comply with FDA regulations for food contact (Blue ,Yellow Y2)
 - * Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI (Blue,Green,Pink,Red,Yellow)
 - * chlorinated for low extractable proteins



Applications: Agriculture, Chemical Industry, Food Industry, Pharmaceutical, Facility maintenance

Elastomer: Natural rubber

Thickness: 0.52 +/- 0.05 mm

Lining: Flocklined

Former: Honeycomb CIH

Exterior: Finished smooth

Cuff Types: Pinked or Straight

Treatments: Un-chlorinated, Chlorinated

Colours: Blue B1, Blue B2, Green G1, Green G3, Orange O1, Pink P2, Red R1, Yellow Y1, Yellow Y2

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 388:2016+A1:2018 ,EN 374-5 : 2016 and EN ISO 21420:2020

Conforms to:

| Physical Dimensions: | Size | Palm | Wrist | Cuff | Length |
|----------------------|-------|------|-------|------|--------|
| | 6-6.5 | 198 | 183 | 248 | 300 |
| | 7-7.5 | 208 | 190 | 251 | 300 |
| | 8-8.5 | 215 | 202 | 268 | 300 |
| | 9-9.5 | 235 | 226 | 280 | 300 |
| | XL | 250 | 237 | 293 | 310 |

Circumference in mm, +/- 5 mm Tol. +/- 10 mm

Shelf Life 3 Years

EN 374-4

| Protection against Chemical hazards | Performance | Degradation % |
|-------------------------------------|-------------|---------------|
|-------------------------------------|-------------|---------------|

EN ISO 374-1/TYP A



| | | |
|------------------------------|---------|------|
| * Methanol (A) | Level 1 | 16.8 |
| * Sodium hydroxide 40% (K) | Level 6 | 14.6 |
| * Sulphuric acid 96% (L) | Level 2 | 36.4 |
| * Nitric acid 65% (M) | Level 5 | 4.8 |
| * Acetic acid 99% (N) | Level 2 | 28.5 |
| * Ammonium hydroxide 25% (O) | Level 1 | -0.1 |
| * Hydrogen peroxide 30% (P) | Level 6 | 31.1 |
| * Formaldehyde 37% (T) | Level 6 | 17.3 |
| * Hydrofluoric acid 40% (S) | Level 6 | X |

Note: Printed copies are valid only on the date printed

Printed Date: 29-Nov-2023

Revision:11

Published Date: 29-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

| Protection against Mechanical hazards | | Performance |
|---------------------------------------|--|-------------|
|---------------------------------------|--|-------------|

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 1
Level 0
Level 1
Level 0
X

| Protection against Micro-organisms risk | | Performance |
|---|--|-------------|
|---|--|-------------|

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
Pass