

Description: Chlorinated/Unchlorinated heavy medium weight flock lined natural rubber gloves

- Features & Benefits:
- \* Anatomically shaped for comfort
  - \* Anti-slip pattern for good grip in wet and dry conditions
  - \* Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI (Orange)
  - \* Fluted Cuff
  - \* Low in soluble proteins
  - \* Natural rubber
  - \* Pure cotton lining to absorb perspiration



Applications: Agriculture, Chemical Industry, Construction, Food Industry, Facility maintenance

Elastomer: Natural rubber

Thickness: 0.55 +/- 0.05 mm

Lining: Flocklined

Former: Sand Patch, CIS

Exterior: Roughened finish

Cuff Types: Straight

Treatments: Un-chlorinated, Chlorinated

Colours: Blue B2, Fluorescent Green G9, Orange O1, Red R1

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN ISO 21420:2020, EN ISO 374-1:2016+A1:2018, EN ISO 374-5:2016 and EN 388:2016+A1:201

Conforms to: ASTM D4679 of 2021

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	S	195	181	249	320
	S+	204	190	252	320
	M	212	201	263	320
	L	228	220	277	320
	L+	246	235	294	320
	XL+	270	256	280	320

Circumference in mm, +/- 5 mm      Tol. +/- 10 mm

Shelf Life 3 Years

EN 374-4

#### Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



* Methanol (A)	Level 2	49.7
* Sodium hydroxide 40% (K)	Level 6	36.3
* Sulphuric acid 96% (L)	Level 3	46.4
* Nitric acid 65% (M)	Level 5	33.5
* Acetic acid 99% (N)	Level 2	17.1
* Ammonium hydroxide 25% (O)	Level 1	-29
* Hydrogen peroxide 30% (P)	Level 6	37.3
* Formaldehyde 37% (T)	Level 6	37.3
* Hydrofluoric acid 40% (S)	Level 6	X

Note: Printed copies are valid only on the date printed

Printed Date: 29-Nov-2023

Revision:6

Published Date: 29-Nov-2023

**DPL**  
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards		Performance
---------------------------------------	--	-------------

EN 388



- \* Abrasion resistance
- \* Blade cut resistance
- \* Tear resistance
- \* Puncture resistance
- \* TDM cut resistance

Level 1  
Level 0  
Level 1  
Level 0  
X

Protection against Micro-organisms risk		Performance
---	--	-------------

EN ISO 374-5



- \* Protection against bacteria and fungi
- \* Protection against viruses

Pass  
n/a