

Description: Medium weight silver lined natural rubber gloves

- Features & Benefits:
- * Anatomically shaped for comfort
 - * Anti-slip pattern for good grip in wet and dry conditions
 - * Bacteriostatic and fungistatic additives
 - * Compliant with (EC) No. 1935/2004, EU 10/2011 & BFR XXI (Black,Pink, Yellow)
 - * Flock free "silver" inner lining for easy-on-easy-off
 - * Ingredients comply with FDA regulations for food contact (Blue only)
 - * Low in soluble proteins
 - * Natural rubber
 - * Pinked or straight cuff

Applications: Agriculture, Chemical Industry, Food Industry, Facility maintenance



Elastomer: Natural rubber

Thickness: 0.50 +/- 0.05 mm

Lining: Silverlined chlorinated

Former: Honeycomb CIH

Exterior: Finished smooth

Cuff Types: Pinked or Straight

Treatments: Chlorinated

Colours: Blue B6, Green G13, Pink P3, Yellow Y3, Yellow Y4

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN ISO 21420:2020, EN ISO 374-1:2016+A1:2018, EN ISO 374-5:2016 and EN 388:2016+A1:2018

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	198	183	248	300
	7-7.5	208	190	251	300
	8-8.5	215	202	268	300
	9-9.5	235	226	280	300
	XL	250	237	293	310

Circumference in mm, +/- 5 mm Tol. +/- 10 mm

Shelf Life 3 Years

EN 374-4

Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYP A



* Methanol (A)	Level 2	53.6
* Sodium hydroxide 40% (K)	Level 6	40.7
* Sulphuric acid 96% (L)	Level 3	62
* Nitric acid 65% (M)	Level 5	57
* Acetic acid 99% (N)	Level 2	46.4
* Ammonium hydroxide 25% (O)	Level 1	20.9
* Hydrogen peroxide 30% (P)	Level 6	40.5
* Formaldehyde 37% (T)	Level 6	42
* Hydrofluoric acid 40% (S)	Level 6	X

Note: Printed copies are valid only on the date printed

Printed Date: 29-Nov-2023

Revision:3

Published Date: 29-Nov-2023




No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964


Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards **Performance**

<p>EN 388</p> 	<ul style="list-style-type: none"> * Abrasion resistance * Blade cut resistance * Tear resistance * Puncture resistance * TDM cut resistance 	<p>Level 1</p> <p>Level 0</p> <p>Level 1</p> <p>Level 1</p> <p>X</p>
---	---	--

Protection against Micro-organisms risk **Performance**

<p>EN ISO 374-5</p> 	<ul style="list-style-type: none"> * Protection against bacteria and fungi * Protection against viruses 	<p>Pass</p> <p>n/a</p>
---	---	------------------------

Note: Printed copies are valid only on the date printed

Printed Date: 29-Nov-2023

Revision:3

Published Date: 29-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com