

Description: Flexible flocklined nitrile gloves, 15mil

- Features & Benefits:
- \* Excellent comfort and flexibility resulting in reduced hand fatigue while being used
  - \* Improved chemical resistivity for a wide range of chemicals
  - \* Outstanding abrasion resistance
  - \* Manufactured under a stringent quality management system
  - \* Antistatic properties according to EN 1149-5:2008
  - \* Compliant with (EC) No.1935/2004, EU 10/2011



Applications: Aerospace and Automobile Industry, Industrial Cleaning, Metal Fabrication, Petrochemical Industry

Elastomer: Nitrile rubber

Thickness: 0.38 +/- 0.05 mm

Lining: Flocklined

Former: Reverse Lozenge, CVIL

Exterior: Finished smooth

Cuff Types: Straight

Treatments: Chlorinated

Colours: Green G8

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 388:2016+A1:2018, EN 374-5 : 2016, EN ISO 21420:2020 and EN 1149-5:2008

Conforms to:


Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6	195	185	284	330
	7	214	206	296	330
	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330

Circumference in mm, +/- 10 mm

Tol. +/- 10 mm

Shelf Life 5 Years

EN 374-4

Protection against Chemical hazards	Performance	Degradation %
EN ISO 374-1/TYPE A		
 * Methanol (A)	Level 2	53.8
* n-Heptane (J)	Level 6	37.9
* Sodium hydroxide 40% (K)	Level 6	25.9
* Sulphuric acid 96% (L)	Level 3	63.4
* Nitric acid 65% (M)	Level 2	89.7
* Acetic acid 99% (N)	Level 3	49.4
* Ammonium hydroxide 25% (O)	Level 6	48.5
* Hydrogen peroxide 30% (P)	Level 6	43
* Formaldehyde 37% (T)	Level 6	-4.6

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023

Revision:11

Published Date: 27-Nov-2023

Protection against Mechanical hazards		Performance
---------------------------------------	--	-------------

EN 388



- \* Abrasion resistance
- \* Blade cut resistance
- \* Tear resistance
- \* Puncture resistance
- \* TDM cut resistance

Level 4  
Level 1  
Level 0  
Level 1  
X

Protection against Micro-organisms risk		Performance
---	--	-------------

EN ISO 374-5



- \* Protection against bacteria and fungi
- \* Protection against viruses

Pass  
n/a