

Manufacture Spec.

Description: Unlined nitrile gloves with tacky finish, 11mil

Features & Benefits:

- * Better grip due to tacky surface
- * Nitrile rubber for better chemical resistance
- * Free of zinc mercaptobenzothiazole
- * Improved sensitivity and dexterity
- * Antislip surface texture for good grip in wet and dry conditions
- * Ingredients comply with FDA regulations for food contact (Blue, Yellow 2, Green)

Applications: Aerospace and Automobile Industry, Food Industry, Industrial Cleaning, Metal Fabrication, Petrochemical Industry, Printing, Surface Coating

Elastomer: Nitrile rubber

Thickness: 0.28 +/- 0.05 mm

Lining: Unlined

Former: Reverse Lozenge, CVIL

Exterior: Tacky finish

Cuff Types: Straight

Treatments: Polymer Coated

Colours: Green G8

AQL - Critical: 1.5

Major: 4.0

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Simple Design) Personal Protective Equipment after assessment internally at DPL's ISO 17025 Accredited Laboratory.

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6	195	185	284	330
	7	214	206	296	330
	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330
		Circumference in mm, +/- 5 mm		Tol. +/- 5 mm	

Permanent Set Value 0 (%):
Shelf Life 5 Years

Moisture Content 0 (%):

Extractable Protein Content 0 (µg/g):

Physical Properties: Tensile strength: 20.0 MPa (min)
Elongation at break: 400% (min)

Modulus at 300% elongation: 6.0 MPa (max)
Load at break: 35.0 N (min)

Protection against Mechanical hazards**Performance**

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance

Level 3
Level 0
Level 0
Level 1

Note: Printed copies are valid only on the date printed

Printed Date: 26-Feb-2024

Revision:6

Published Date: 21-Feb-2024



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com