

Manufacture Spec.

Description: Bi-colour chlorinated heavy medium weight bead rolled flocklined nitrile over natural rubber gloves

Features & Benefits: * Nitrile over natural rubber

- * Anatomically shaped for comfort
- * Pure cotton lining to absorb perspiration
- * Anti-slip pattern for good grip in wet and dry conditions
- * Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
- * Chlorinated for enhanced chemical resistance
- * Low in soluble proteins

Applications: Horticulture, Household applications, Facility maintenance

Elastomer: Natural/Nitrile blended rubber

Thickness: 0.55 +/- 0.05 mm

Lining: Flocklined

Former: Picot, CIQ

Exterior: Finished smooth

Cuff Types: Bead rolled

Treatments: Chlorinated

Colours: Mauve on Mauve M3/M2, Yellow on Yellow Y7/Y6

AQL - Critical: 1.5

Major: 4



CE Certification: Conforms to PPE Regulation EU 2016/425 to (Simple Design) Personal Protective Equipment after assessment internally at DPL's ISO 17025 Accredited Laboratory.

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	211	201	260	330
	7-7.5	229	222	266	330
	8-8.5	194	180	242	330
	9-9.5	246	235	290	330
	XL	203	188	246	330

Circumference in mm, +/- 5 mm Tol. +/- 5 mm

Permanent Set Value 6 (%):
Shelf Life 3 Years

Moisture Content 0.6 (%):

Extractable Protein Content 100 (µg/g):

Physical Properties: Tensile strength: 18.0 MPa (min)
Elongation at break: 700% (min)

Modulus at 500% elongation: 6.0 MPa (max)
Load at break: 50.0 N (min)

Protection against Chemical hazards

Performance

Degradation %

EN 374

- * Sulphuric acid 96% (L)
- * Sodium hydroxide 40% (K)
- * Methanol (A)

Level 2

0

Level 4

0

Level 0

0

Note: Printed copies are valid only on the date printed

Printed Date: 26-Feb-2024

Revision:2

Published Date: 21-Feb-2024



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Manufacture Spec.

Protection against Mechanical hazards Performance

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance

Level 2
Level 0
Level 1
Level 0

Protection against Micro-organisms risk Performance

EN 374



- * Air leak test
- * Water leak test

Passed
Passed