LINEPRO (Class 3)

61292-M00-VB-360

CURRENT

06-July-2017

Description: Rubber insulating gloves

Features & * Made with special grade natural rubber compounds for assured electrical protection

Benefits: * Superior anatomical construction results in lower hand fatigue

* Higher flexibility for long duration wear comfort

* 100% QC Inspection

* Packed in opaque UV resistant bags and individual boxes for product protection

* Each glove is inspected/tested for electrical insulation

* Electrical tests are performed on premium grade test machine custom made in USA (NO81A1-D)

* Compliant to ASTM D 120

* Manufactured on a purpose built production line

* Produced at an ISO 9001:2015/ISO 14001:2015 accredited facility

Applications: For power companies (utilities), Electrical workshops, Insulation, Maintenance and Repairs involving

High Voltage Equipment

Product Details:

Elastomer: Natural rubber Thickness: 2.92 mm (max)

Lining: Unlined chlorinated

Former: Plain smooth

Cuff type: Straight

Exterior: Chlorinated

Colours: Black, Red, Natural

Type/Category: Type 1

Proof test voltage AC: 30000 V Max. use voltage AC: 26500 V

Physical Dimensions :	Size	Palm	Wrist	Cuff	Length
	8	206	206	379	360
	8 1/2	217	217	379	360
	9	227	227	392	360
	9 1/2	243	243	395	360
	10	251	251	396	360
	10 1/2	266	266	403	360
	11	282	282	405	360

Internal circumference in mm,+/- 13 Tolerance +/- 13 mm

Physical Properties: Tensile strength 17.2 MPa (min) Tension set 25% (max)

Elongation at break 600% (min)

Arc Flash Protection (Assessed according to EN 61482-1-2): APC 2

Issue No: 1 Date:06-July-2017 Amendment No: 1 Date:10-Feb-2023

Phone: +94-0122-683-964 Fax: +94-0122-699-018 E-Mail: postmast@dplgroup.com

